

Link Technical Data - W3-LNK-NNN



Link Technical Data



Model Numbers: W3-LNK-NNN-N

Device Parameters

Dimensions (mm) HxWxD:	235 x 161 x 58 (excl. antenna 81mm and USB 15mm)
Weight:	1.4kg
Operating temperature:	-25°C to +70°C
Humidity:	Relative humidity >95% non-condensing (25°C to 55°C)

Supply Parameters

Operating voltage range:	4.4-6.4V from internal battery
Power:	620μW average
Current consumption:	120μA average
Battery type:	Alkaline primary cells, 23Ah

RF Parameters

Operating frequency:	916.5MHz
Transmit power:	25mW max
Duty cycle:	<1%
Encryption:	None
Channel spacing:	Single channel
Compatible with:	Other WES3 units
Protocol:	Proprietary

Link Technical Data - W3-LNK-NNN



Model Numbers: W3-LNK-NNN

Device Parameters

Dimensions (mm) HxWxD:	235 x 161 x 58 (excl. antenna 81mm and USB 15mm)
Weight:	800g
Operating temperature:	-25°C to +70°C
Humidity:	Relative humidity >95% non-condensing (25°C to 55°C)

Supply Parameters

Operating voltage range:	4.4-6.4V from internal battery
Power:	600µW average
Current consumption:	110µW average
Battery type:	Alkaline primary cells, 7.6Ah

RF Parameters

Operating frequency:	916.5MHz
Transmit power:	25mW max
Duty cycle:	<1%
Encryption:	None
Channel spacing:	Single channel
Compatible with:	Other WES3 units
Protocol:	Proprietary