



## Emergency Control Unit Technical Data

Model Numbers: W3-SCU-STD

### Device Parameters

Dimensions (mm) HxWxD:	235 x 161 x 128 (excl. antenna 81mm and USB 15mm)
Weight:	1.5kg
Operating temperature:	-13°F to +158°F (-25°C to +70°C)
Humidity:	Relative humidity >95% (77°F to 131°F)

### Supply Parameters

Operating voltage range:	4.4-6.4V from internal battery
Power:	620µW average
Current consumption:	120µA average
Battery type:	Alkaline primary cells, 23Ah

### RF Parameters

Operating frequency:	916.5MHz
Transmit power:	25mW max
Duty cycle:	<1%
Encryption:	None
Channel spacing:	Single channel
Compatible with:	Other WES <sup>3</sup> units
Protocol:	Proprietary

The Radio Frequency (RF) range complies with the Phase II EGSM 900/DCS 1800 recommendation. The frequency range for the transmit band and the receive band are listed in the table below:

	Transmit Band (Tx)	Receive Band	Power
E-GSM 900	880 to 915 MHz	925 to 960 MHz	2 Watts EGSM 900 radio section
DCS 1800	1710 to 1785 MHz	1805 to 1680 MHz	1 Watt GSM1800 radio section